

## CELBINDER 15 E

Is a acrylic binder for pigment printing/coating, with soft handle and good fastness properties. Also used as a antipilling agent, body agent applied in all kind of finishing process.

CHARACTERISTICS	BENEFITS
Soft hand feel and good wet & dry rub fastness.	Better then other alternate acrylic binder and low consumption.
Bright color yield and clear articulation.	User friendly
For all climates, odor free and stability.	Wide range application.
Eco-friendly, APEO free, GOTS 5 approved and no formaldehyde content (Oekotex Class 1).	Environmental friendly product

## PROPERTIES

Appearance	White Flowable Liquid
pH (Emerck Strips 2.0 - 9.0)	5.0 - 7.0
Ionic	anionic
Ecology	It is a non-toxicity, non-pollution, and environmental product. General chemicals operations should be obeyed while storing, transporting, and using.
Storage stability:	Be packed in plastic casks of 50kg with well-closed package of plastic bag inside. This product should be kept in shady, cool and dry places, with temperature 5-40°C. It should be used up within twelve months

## APPLICATION:

Versatile product can be used in padding , coating and printing for every kind of substrate.

## USING METHOD:

Regular used quantity is 2-15% in coating and printing.  
Special used quantity is 10 – 40 gpl in padding as antipilling agent.

## **NOTE:**

The above information is approved. Due to the different technology applied in different mill, the customers should make sure to take the right processing before using them.

## **ATTENTION**

The information given above is in line with our present state of knowledge and experience and is without any guarantee. Users must thoroughly test any application before any commercialization. We are not liable for damages due to improper application of our products.